

## Ergomat Basic Mat

Ergomat Basic Mats are light-duty ergonomic and anti-fatigue mats that perform well in non-demanding applications like retail counters, pick lines, mail rooms and other typical office functions. When used according to published specifications Basic Mats will never curl, rip, disintegrate or create a trip hazard. Available in 3 profiles: **Bubble**, **Smooth** and **Bubble Down**.



- BUBBLE
- SMOOTH
- BUBBLE DOWN



### 3 Profiles

Bubble

Smooth

Basic Bubble Down



Thickness .57" (1.45 cm)



Thickness .43" (1.1 cm)



Thickness .625" (1.5 cm)  
2" (5cm) Yellow Bevels

### BENEFITS

**ERGONOMIC** : Designed to stimulate circulation in feet, legs and lower back. Circulation is stimulated by the unique, patented surface profile of Ergomat mats, which forces muscular response.

**BEVELED EDGES** : Molded w/ bevels. The Basic Bubble Down mat always comes with 2" (5cm) yellow bevels. Bevels will never curl up, eliminating trip hazards.

**GREAT RETAIL MATTING** : Smooth top surface makes Basic Bubble Down and Basic Smooth profiles ideal for pivoting workers, in non-demanding work environments

**ANY SIZE ANY SHAPE**: Can be custom made to any size and shape, creating one continuous surface to eliminate seams and trip hazards.

**SILICON FREE**: All Ergomat mats are silicon free.

**TRUE WARRANTY**: Ergomat stands 100% behind our products with full replacement coverage if our product fails to perform as promoted within that period. At Ergomat we call this a *True Warranty*.

[www.ergomat.se](http://www.ergomat.se) - [info@ergomat.se](mailto:info@ergomat.se)

North & South America: +1-440-282-4651 | English (EU): +44 3308 280 084 | Danish: +45 702 21 840 | Dutch: +31 73 61 30 530 | Swedish: +46 42 16 36 00  
 German: +49 9542 30 367-50 | French: +33 1 446 410 28

# Ergomat Basic Mat

	SMOOTH	BUBBLE	BASIC BUBBLE DOWN
Material.....	Foamed Polyurethane		
Color.....	Grey		Grey w/ Yellow Bevels
Weight.....	1900 g +/- 50 g // 4.2 lbs +/- 0.1 lbs	2100 g +/- 50 g // 4.63 lbs +/- 0.1 lbs	2100 g +/- 50 g // 4.63 lbs +/- 0.1 lbs
Length without beveled edges..	91 cm +/- 1% // 35.8" +/- 0.38"		
Width without beveled edges...	60 cm +/- 1% // 23.6" +/- 0.38"		
Thickness.....	11 mm // 0.43"	14,5 mm // 0.57"	15 mm // 0.625"
Density.....	330 kg/m <sup>3</sup> +/- 10 % ISO 2781		
Hardness.....	18-28 Sh A DIN 53505		
Abrasion Load = 5 N.....	800 mm <sup>3</sup> // 31.5 in <sup>3</sup> ISO 46 49 (5 N)		
Electrical Resistance Surface point to point % 50 RH.....	>20x10 <sup>9</sup> Ω IEC-61340 4-1/ ESD STM7.1-2001		
Breaking Point/Tensile Strength	1 Mpa EN ISO 527-1		
Elongation at Break.....	200% EN ISO 527-1		
Tearing Strength.....	1,5 N/mm ASTM D 624		
Thermal Properties.....			
Minimum use.....	0°C // 32°F		
Maximum use.....	32°C // 90°F		
Maximum short duration	40°C // 115°F		
UV-Resistance.....	Inferior		
Warranty.....	2 years		