




Ergomat Infinity Mat

Infinity Series mats are durable polyurethane ergonomic mats with a closed cell surface that resists light moisture and most chemical exposures. Available in ESD version and 3 profiles: Deluxe, Smooth and Bubble.



3 Profiles

Infinity Deluxe



Thickness .62" (1.5cm)

Infinity Smooth



Thickness .43" (1.1cm)

Infinity Bubble



Thickness .57" (1.45cm)

BENEFITS

ESD OPTION: Engineered with enhanced static control. Electrical resistance : $3 \times 10^8 \Omega - 8 \times 10^8 \Omega$

ERGONOMIC: Designed to stimulate circulation in feet, legs and lower back. Circulation is stimulated by the unique, patented surface profile of Ergomat mats, which forces muscular response.

BEVELED EDGES: Molded w/ bevels. Yellow bevels can be added. Bevels will never curl up, eliminating trip hazards.

ISO CLEANROOM CERTIFIED: Infinity mats are ISO Cleanroom Class 5 (Class 100) rated.

ANY SIZE ANY SHAPE: Can be custom made in any size and shape, creating one continuous surface to eliminate seams and trip hazards.

SILICON FREE: All Ergomat mats are silicon free.

TRUE WARRANTY: Ergomat stands 100% behind our products with full replacement coverage if our product fails to perform as promoted within that period. At Ergomat we call this a *True Warranty*.

www.ergomat.se - info@ergomat.se

North & South America: +1-440-282-4651 | English (EU): +44 3308 280 084 | Danish: +45 702 21 840 | Dutch: +31 73 61 30 530 | Swedish: +46 42 16 36 00
 German: +49 9542 30 367-50 | French: +33 1 446 410 28

ERGOMAT INFINITY

SMOOTH

BUBBLE

SMOOTH ESD

BUBBLE ESD

INFINITY DELUXE

Material.....	Foamed Polyurethane				
Color.....	Black, Silver, White, Blue, Yellow, Red, Stainless, Brown, Green		Black, Silver, White, Stainless, Blue	Black, Silver, White, Stainless, Blue	Black, Silver, Stainless, Blue
Weight.....	2200 g +/- 50g // 4.85 lbs +/- 0.1 lbs	2600 g +/- 50 g // 5.7 lbs +/- 0.1 lbs	2200 g +/- 50g // 4.85 lbs +/- 0.1 lbs	2600 g +/- 50 g // 5.7 lbs +/- 0.1 lbs	2775 g +/- 50 g // 6.1 lbs +/- 0.1 lbs
Length without beveled edges.....	91 cm +/- 1% // 35.8" +/- 0.38"				
Width without beveled edges.....	60 cm +/- 1% // 23.6" +/- 0.38"				
Thickness.....	1.1 cm // 0.43"	1.45 cm // 0.57"	11 mm // 0.43"	1.45 cm // 0.57"	1.5 cm // 0.62"
Density.....	400 kg/m ³ +/- 10 % ISO 2781				
Hardness.....	37-45 Sh A DIN 53505				33-38 Sh A
Surface Durability.....	30 m DIN 4649 test equipment with 2,5N load				
Electrical Resistance Surface point to point % 50 RH.....	3x10 ⁸ Ω-8x10 ⁹ Ω IEC-61340 4-1/ ESD STM7.1-2001	3x10 ⁹ Ω-5x10 ⁹ Ω IEC-61340 4-1/ ESD STM7.1-2001	3x10 ⁸ Ω-8x10 ⁹ Ω IEC-61340 4-1/ ESD STM7.1-2001	3x10 ⁸ Ω-8x10 ⁹ Ω IEC-61340 4-1/ ESD STM7.1-2001	3x10 ⁹ Ω-5x10 ⁹ Ω IEC-61340 4-1/ ESD STM7.1-2001
Fire Behavior.....	Cfl-s1(B) EN 13501-1 (DIN 4102-B1 Part 14)				
Thermal Properties					
Minimum use.....	0°C // 32°F				
Maximum use.....	32°C // 90°F				
Maximum short duration.....	40°C // 115°F				
Cleanroom Application.....	ISO Class 5 (100) EN ISO 14644-1				
Warranty.....	6 years, 12 years for retail environment				